

Gillison's Variety Fabrication, Inc.

Manufacturers of quality farm equipment since 1977.

GVF HEDGERS TOPPERS & SKIRTERS

Presenting the extensive line of GVF hedgers. This rugged equipment will hedge, top or skirt the following: Cherries, Pears, Peaches, Olives, Apples, Raspberries, Nut Trees, Prunes, Citrus, Grapes, Coffee, Oleander, Lychee, Longan, etc.

- Heavy tubular steel construction with rigid tractor mount.
- Electric/Hydraulic controls for ease of installation and operator comfort.
- Equipped with independent self contained hydraulic system.
- Standard hydraulic breakaway protection for hedging.
- Cutting heads can be set along side of tractor for transporting.
- Recommended cutting capacity of up to 1 1/2" diameter limbs.
- Proven dual sickle drive system.
- Any cutter bar length available from 2' to 15'
- 1 year warranty
- Options
 - Magnum cutting head with 30% more cutting capability



Grape Hedger and Cane Positioner



Standard Topper-Hedger



Dual Hedger



Loader Mount Hedger



Pecan Hedger











Double Topper-Hedgers



3 Point Skirter



Hedger and Skirter

								
Type of independent, self contained hydraulic system	Dual	Triple	Dual	Dual	Single	Single	Single	Single
Break away protection	None	None	None	None	Standard	Standard	None	Optional
Movement of cutter head	360° Rotation Side shift to 4'	360° Rotation (self leveling head) Side shift 4'	360° Rotation (self leveling head) Side shift 4'	Tilt & Slide	Tilt 110°	Tilt 110°	Lift, tilt & side shift	Lift & tilt (optional 3' movement in & out)
Standard cutter bar length	10' (any length from 2' to 15' available as option)	10' (any length from 2' to 15' available as option)	12' (any length from 2' to 15' available as option)	10' with 3' lower bar extension (any length from 2' to 15' available as option)	7' (any length from 2' to 15' available as option)	7' (any length from 2' to 15' available as option)	4'	7' (any length from 2' to 15' available as option)
Topping & hedging capabilities	18' topping	20' topping of 2 rows	Side hedge to 36', top hedge to 24'	Widths: 2'-4', 4'-8', 5' - 11' (custom widths available)	Skirt as low as 12"	Side hedge to 12' (with 7' bar) Skirt as low as 12" Flat top 6'	9'	Max height determined by loader's max height
Cutting capabilities	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	3/4"	1 1/2"
Mount type	Rear, custom mounted frameworks, easily dismounts from tractor.	Rear, custom mounted frameworks, easily dismounts from tractor.	Rear, custom mounted frameworks, easily dismounts from tractor.	Front, custom mounted frameworks, easily dismounts from tractor.	Rear	Front	Front	Loader
Safety lock systems on hydraulic functions	Standard	Standard	Standard	n/a	n/a	n/a	n/a	n/a

Sold & Serviced By: