



Gillison's Variety Fabrication, Inc.

Manufacturers of quality farm equipment since 1977.

GVF HEDGERS TOPPERS & SKIRTTERS

Presenting the extensive line of GVF hedgers. This rugged equipment will hedge, top or skirt the following: Cherries, Pears, Peaches, Olives, Apples, Raspberries, Nut Trees, Prunes, Citrus, Grapes, Coffee, Oleander, Lychee, Longan, etc.

GVF Hedgers, Toppers & Skirters

- Heavy tubular steel construction with rigid tractor mount.
- Electric/Hydraulic controls for ease of installation and operator comfort.
- Equipped with independent self contained hydraulic system.
- Cutting heads can be set along side of tractor for transporting.
- Recommended cutting capacity of up to 1 1/2" diameter limbs.
- Proven dual sickle drive system.
- Any cutter bar length available from 2' to 15'.
- 1 year warranty.
- Options
 - Magnum cutting head with 30% more cutting capability.

Featuring: GVF Center Mount Topper and Hedger



GVF Center Mount Topper and Hedger What's so great about it?



- High tensile strength steel and rigid tractor mount.
- New narrow boom design that reduces tree damage and improves operator visibility.
- Width of 3'6" on either side of the tractor or 7' overall.
- Height adjustment range of 3'6" to 20'.
- 360° rotation allows for topping or hedging.
- Excellent visibility.
- Fork pockets for easy installation.
- Easily attaches to 3 point hitch and top link.
- New high efficiency hydraulic system that allows for smooth operation and cutting head speed that is independent of the tractor.
- Oil cooler comes standard.



Double Topper-Hedger



Dual Hedger



Loader Mount Hedger




Pecan Hedger



Double Topper-Hedger



3 Point Skirter



Grape Hedger
and Cane Positioner



Hedger and Skirter



	Center Mount Topper-Hedger	Double Topper-Hedger	Pecan Topper-Hedger	Dual Hedger	3 Pt. Skirter	Hedger and Skirter	Grape Hedger and Cane Positioner	Loader Mount Hedger
Type of independent, self contained hydraulic system	Closed center piston pump design.	Triple	Dual	Dual	Single	Single	Single	Single
Break away protection	None	None	None	None	Standard	Standard	None	Optional
Movement of the cutter head	360° Rotation Side shift 3'6" on either side of the tractor; 7' overall	360° Rotation (self leveling head) Side shift 4'	Rotation	Tilt & Slide	Tilt 110°	Tilt 110°	Lift, tilt & side shift	Lift & tilt (optional 3' movement in & out)
Standard cutter bar length • Any length from 2' to 15' available as an option.	10'	10'	12'	10' with 3' lower bar extension	7'	7'	4'	7'
Topping & hedging capabilities	Height adjustment of 3'6" to 20'. Maximum flat topping height of 20'.	20' topping of 2 rows		Widths: 2'-4', 4'-8', 5'-11' (custom widths available)	Skirt as low as 12"	Side hedge to 12' (with 7" bar) Skirt as low as 12" Flat top 6'	9'	Max height determined by loader's max height
Cutting capabilities	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	1 1/2"	3/4"	1 1/2"
Mount type	Fork pockets for easy installation. Attaches to 3 point hitch and top link.	Rear, custom mounted frameworks, easily dismounts from tractor.	Rear, custom mounted frameworks, easily dismounts from tractor.	Front, custom mounted frameworks, easily dismounts from tractor.	Rear	Front	Front	Loader
Safety lock systems on hydraulic functions	Standard	Standard	Standard	n/a	n/a	n/a	n/a	n/a