



Gillison's Variety
Fabrication, Inc.

Manufacturers of quality farm equipment since 1977.

ROUGH TERRAIN FORKLIFTS

GVF Rough Terrain Forklifts are fast, powerful machines that operate smoothly. These lifts get the job done quickly and comfortably and now offer Tier IV engines.


- Models: GVF 5000, 6000 & 8000, available in 2WD and 4WD.
- JCB 444 Tier IV EcoMax engine, 74 HP
- 20% more torque than the previous Tier III engine.
- Roomier operators platform; 4" wider than before offering better visibility and more elbow room.
- Solid top overhead with a window.
- Fuel system: high pressure common rail
- No exhaust after-treatment
- Extended service intervals
- High efficiency, excellent fuel economy
- See through mast
- 48" carriage with 6 rollers
- 8" side shift in carriage
- Independent power assisted braking which allows operator to use the brakes for turning and decreases pedal effort required for braking which results in better performance and less operator fatigue.
- LED flood lights - front & rear
- LED direction indicator lights
- LED warning flasher lights
- Backup alarm
- Horn
- Tilt and telescoping steering column
- Suspension seat
- Engine pre cleaner
- Grid heater for cold start
- Vertical exhaust
- Rear view mirror
- 4 section hydraulic valve
- 150 cu. in. tool box
- Painted with high quality urethane paint
- Unrivaled reliability
- Options:
 - 2 or 4 wheel drive
 - Front fender extensions
 - Warning beacon
 - Transmission brake
 - Bin clamp
 - Load backrest
 - Bin dumper
 - Soft Ride
 - Rear fender
 - Tire Upgrade



GVF 5000 Forklifts shown with bin clamps.



The Unrivaled GVF Forklifts Offer:
Tier IV engines!
Fast mast cycle speeds!
Exceptional turning radius!
Extremely good visibility!
Fast directional changes!
Easy braking!



SPECIFICATIONS		Drawing Reference Number	GVF 5000	GVF 6000	GVF 8000
Overall length (without forks)		1	139.5"	139.5"	158"
Overall width		2	80"	80"	87"
Wheel base		3	84"		
Height to top overhead guard		4	102"		
Clearance under counterweight		5	18.5"		
Transmission clearance		6	18.5"		
Clearance under mast		7	13"		
Weight			12,000 lbs.	13,000 lbs.	16,190 lbs.
Lift capacity @ 24" load center			5,000 lbs.	6,000 lbs.	8,000 lbs.
Mast tilt forward			30°	30°	25°
Mast tilt rearward			11°	11°	12°
Mast side shift			8"		
Outside turning radius			12'		
Standard lift height			12'		
Travel speed			18.5 MPH		
Tire Size	GVF 5000 & 6000: Drive: 16.9-24, 10 ply, R4 Steer: 12.5-80R-18, 10 ply, R4		GVF 8000: Drive: 19.5L-24, 10 ply, R4 Steer: 12.5-80R-18, 10 ply, R4		
Steering	Load sense power steering, 2.5 turns lock to lock				

Engine Manufacturer & Model	JCB 444 Tier IV EcoMax
Cylinders	4
Fuel system	High pressure common rail
Engine gross HP	74 @ 2200 RPMs
Peak torque	295 lb/ft @ 1200 RPMs
Start aid cold weather	Grid heater
Transmission	4-speed synchro-shuttle
Fuel tank capacity	25 gallons
Parking brake	External disc
Front axle	Self locking torque proportioning differential internal wet disc brake
Rear axle	4 wd self locking torque proportioning differential 20° oscillation
Hydraulic pump	24 gpm @ 2200 RPMs
Control valve	4 section, 1 aux
System pressure	2600 psi
Electrical	
Voltage	12 volt
Alternator	95 amp
Battery rating	950 cca

2 or 4 wheel drive models available.