

GVF 11005
WORK PLATFORM
AND
GVF 11020
MOTORIZED CART
SECTION

A mobile work platform designed with the maintenance of trellised apples in mind.

- 84" outside width.
- Width adjustment Can slide up to 102" wide.
- One worker can control the speed and steering at thier level.
 No need for a dedicated driver.
- Upper controls include shut-off switch, brake switch, steering and forward and reverse travel speeds.
- Allows up to three people per side at different working elevations.
- Maximum working platform height is 48" and minimum is 18".
- Platforms feature 4" toe kick, 39" railing and a mid-railing for safety.
- Rugged tube frame construction.
- Light and easy to maneuver.
- Built for easy maintenance.
- External fuel and oil tanks with screens in filler caps and drains in the bottom of the tanks.
- Fuel system has inline 10 micron filter to prevent contamination.
- Kawasaki 16.4 HP air cooled engine.
- Speed: 0 to 9 MPH
- If conversion to a picking cart is desired, adding the wings is completed simply with nuts & bolts.
 No cutting or welding or other adaptations are needed.







Hydraulic System These features come standard to provide you with years of use.

- Hydrostatic drive with closed loop axial piston pump mechanically controlled.
- Wheel motors radial piston with integral park brake.
- Hydraulic filter
- Oil cooler
- Hot oil shuttle to keep closed loop cool and supplied with fresh oil.

Designed with ease of maintenance in mind.

- All pivot points are accessible for quick greasing.
- Steering system incorporates DX bushings and can be easily taken apart for maintenance.





